

**DECLARATION OF PERFORMANCE**  
**No. 04/2016/ND**

1. Unique identification code of the product – type: **135**
2. Intended use or uses:
  - 2.1. Flexible sheets for waterproofing – Underlays for discontinuous roofing according to EN 13859-1: 2010
    - 2.1.1. As a precoat, sealing roof coverings which are based on battens and counter-battens (MWK) i non-ventilated roofs and in ventilated roofs with ventilated coverings.
    - 2.1.2. As a protective – spacer layer of thermal insulation under coverings based on sheathings in ventilated roofs with a slope >10°.
    - 2.1.3. As a sealing of coverings laid on contact with sheathing – under tiles e.g. of slate, sheet, fiber cement etc. in ventilated and non-ventilated roofs.
    - 2.1.4. As a sealing of plates of „on-rafter” thermal insulation, e.g. PIR, PUR etc. according to manufacturer’s instructions.
  - 2.2. Flexible sheets for waterproofing – Underlays for walls according to EN 13859-2: 2010
    - 2.2.1. As a wind-insulation (draft-tight layer) in stud walls of wooden or metal construction;
    - 2.2.2. As a sealing and protection of thermal insulation in wooden and concrete ceilings.
3. Manufacturer:
 

Info-GLOBAL sp. j.  
ul. Długa 67  
63-400 Ostrów Wielkopolski  
tel. +48 62 737 27 60 fax. +48 62 737 27 61  
Production plant : ul. Szypowskiego 1, 39-460 Nowa Dęba
4. System of assessment and verification of constancy of performance:
 

Conformity assessment system 3.
5. Harmonized standard:
 

EN 13859-1: 2010 Flexible sheets for waterproofing. Definitions and characteristics of underlays. Part 1: Underlays for discontinuous roofing.

EN 13859-2: 2010 Flexible sheets for waterproofing. Definitions and characteristics of underlays. Part 2: Underlays for walls.

Notified body or bodies:

Polskie Centrum Badań i Certyfikacji S.A. Oddział Badań i Certyfikacji w Gdańsku Laboratorium Wytrobów Budowlanych, ul. Wejhera 18a, 80-346 Gdańsk, nr 1434.
6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	EN 13859-1: 2010 EN 13859-2: 2010
Water tightness	W1	
Tensile properties: - along - across	280 +60/- 80 [N/50 mm] 190 +60/- 80 [N/50 mm]	
Elongation: -along -across	70 +/- 40 [%] 90 +/- 40 [%]	
Water vapour transmission – Sd parameter, i.e. diffusively equivalent air layer thickness	0,015 + 0,02/ - 0,01 [m]	

Resistance to tearing: - along - across	180 +/- 70 [N] 230 +/-70 [N]	
Flexibility at low temperature	- 25 [°C]	
Resistance to artificial ageing: Tensile properties: - along - across	230 +/- 80 [N/50 mm] 150 +/- 80 [N/50 mm]	
Elongation: -along - across	50 +/- 30 [%] 70 +/- 40 [%]	
Water tightness	W1	

The performances of the product identified above are in conformity with the set of declared performances . This declaration of performance is issued according to the regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer indicated above.

The copy of declaration of performance can be found on the manufacturer's website:  
[www.himalayanroof.pl](http://www.himalayanroof.pl)

Signed on behalf of the manufacturer by:



Szymon Jaś, Product Manager  
Ostrów Wielkopolski, 20.05.2016