

DECLARATION OF PERFORMANCE
No. 07/2016/ND

1. Unique identification code of the product – type: **185**
2. Intended use or uses:
 - 2.1. Flexible sheets for waterproofing – Underlays for discontinuous roofing according to EN 13859-1: 2010
 - 2.1.1. As a precoat, sealing roof coverings which are based on battens and counter-battens (MWK) i non-ventilated roofs and in ventilated roofs with ventilated coverings.
 - 2.1.2. As a protective – spacer layer of thermal insulation under coverings based on sheathings in ventilated roofs with a slope > 5°.
 - 2.1.3. As a sealing of coverings laid on contact with sheathing – under tiles e.g. of slate, sheet, fiber cement etc. in ventilated and non-ventilated roofs.
 - 2.1.4. As a sealing of plates of „on-rafter” thermal insulation, e.g. PIR, PUR etc. according to manufacturer’s instructions.
3. Manufacturer:

Info-GLOBAL sp. j.
ul. Długa 67
63-400 Ostrów Wielkopolski
tel. +48 62 737 27 60 fax. +48 62 737 27 61
Production plant: ul. Szypowskiego 1, 39-460 Nowa Dęba
4. System of assessment and verification of constancy of performance:

Conformity assessment system 3.
5. Harmonized standard:

EN 13859-1: 2010 Flexible sheets for waterproofing. Definitions and characteristics of underlays. Part 1: Underlays for discontinuous roofing.

Notified body or bodies:

Polskie Centrum Badań i Certyfikacji S.A. Oddział Badań i Certyfikacji w Gdańsku Laboratorium Wytrobów Budowlanych, ul. Wejhera 18a, 80-346 Gdańsk, nr 1434.
6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	EN 13859-1: 2010
Water tightness	W1	
Tensile properties: - along - across	380 +/- 80 [N/50 mm] 270 +/- 80 [N/50 mm]	
Elongation: -along -across	70 +/- 40 [%] 90 +/- 40 [%]	
Resistance to tearing: - along - across	240 +/- 90 [N] 310 +/-90 [N]	
Flexibility at low temperature	- 25 [°C]	

Resistance to artificial ageing:		
Tensile properties:		
- along	350 +/- 100 [N/50 mm]	
- across	220 +/- 100 [N/50 mm]	
Elongation:		
-along	50 + 40/- 30 [%]	
- across	70 + 40/- 30 [%]	
Water tightness	W1	

The performances of the product identified above are in conformity with the set of declared performances . This declaration of performance is issued according to the regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer indicated above.

The copy of declaration of performance can be found on the manufacturer's website:

www.himalayanroof.pl

Signed on behalf of the manufacturer by:



Szymon Jaś, Product Manager
Ostrów Wielkopolski, 05.09.2016